### **DIKGATLONG LOCAL MUNICIPALITY**



# RE-ADVERTISMENT: FORMAL WRITTEN PRICE QUOTATION FOR SEVEN DAYS NOTICE BID NO: RFQ17/2023/24

**Dikgatlong Municipality** hereby invites suitably prospective service providers to quote for supply and delivery of electrical material in Barkly West. **Sealed** Price quotations clearly marked "RFQ17/2023/24 SUPPLY AND DELIVERY OF ELECTRICAL MATERIALS" clearly endorsed on the envelope" must be submitted to the Dikgatlong Local Municipality, 33 Campbell Street, Barkly West, 8375. Bids **must** reach the municipality before *12h00 on Friday the 16<sup>th</sup> of* February 2024.

#### **BACKGROUND AND SPECIFICATIONS/ SCOPE OF WORK**

Item no	Qty	Description
1	1	<ul> <li>Portable Working Earth Kit (1-33KV) which includes</li> <li>4 x 2m Phase leads of 16mm2 flexible copper insulated with snap on clamps both sides.</li> <li>2 x 10m Phase to cluster bar leads of 16mm2 flexible copper insulated with snap on clamps one side and earth clamps on the other side.</li> <li>1 x 4m Cluster bar to earth rod lead of 16mm2 flexible copper insulated with earth clamps on both sides.</li> <li>1 x Cluster bar</li> <li>1 x Cluster head</li> <li>1 x Heavy duty carry bag</li> </ul>
2	30	AC Circuit Breaker 63A.  Complies with AC protection IEC 60947-2 and switch disconnect IEC 60947-3  1 Pole Top and bottom connection Mounting: din rail/ mini rail (26mm) Insulated voltage: 240/415 V  KA Rating: 6KA Curve 2  QF range dual mount high ratings 26 MM hydraulic-magnetic

3	30	AC Circuit Breaker 80A.		
		<ul> <li>Complies with AC protection IEC 60947-2 and switch disconnect IEC 60947-3</li> <li>1 Pole</li> <li>Top and bottom connection</li> <li>Mounting: din rail/ mini rail (26mm)</li> <li>Insulated voltage: 240/415 V</li> <li>kA Rating: 6KA</li> <li>Curve 2</li> <li>QF range dual mount high ratings 26 MM hydraulic-magnetic</li> </ul>		
4	500m	<ul> <li>ABC 70mm square Ariel Bundle Conductor, with bare neutral + street light conductor</li> <li>Complies with SANS 1507 -6</li> </ul>		
5	50	Suspension Clamp bare neutral 50-70mm		
6	25	ABC Strain clamp bare neutral		
7	500m	<ul> <li>10mm squared SNE + solid pilot Airdac</li> <li>Complies with SANS 1507 -6</li> </ul>		
8	25	Pigtail bolt M16x380mm		
9	6	Dropout Fuse silicone cut-out carrier 11KV		
10	30	Fuse links, solid button 15A/ 11KV		
11	15	Fuse link, solid button 65A/ 11KV		
12	30	Fuse link, solid button 25A/ 11 KV		
13	50	Insulation Piercing Clamp 25- 95mm		
14	50	PG clamps 2 bolts 4-15mm aluminium		
15	30	70x16 aluminium lugs		
16	30	70 mm ferrules		
17	100	16 mm ferrules		
18	50	35mm ferrules		
19	30	25 mm ferrules		
20	10	Red insulation tape		
21	10	Black insulation tape		
22	10	Yellow insulation tape		
23	10	Blue insulation tape		
24	2	Wire grip Come along		
25	1	1500 kg lever hoist ratchet		

26	2	Three Phase Circuit Breaker	
	_		
		300A rated current	
		25KA rating  ALEV rate departies walter as A.C.	
		415V rated service voltage AC     Fraguency 50H7	
		Frequency 50HZ  The great report of the trip continue to the continue to	
		Thermal magnetic trip unit     Elevible connection Coller terminals front and rear connections etraight connections.	
		<ul> <li>Flexible connection Collar terminals, front and rear connections, straight connections, spreaders, plug in</li> </ul>	
		Earth leakage protection	
		Rated insulation voltage 690V	
		Storage temperature -25°C to +70°C	
		Operating temperature -5°C to +60°C	
27	1 Three Phase Circuit Breaker		
		FOOA rated oursest	
		<ul><li>500A rated current</li><li>35KA rating</li></ul>	
		<ul> <li>35KA rating</li> <li>415V rated service voltage AC</li> </ul>	
		Frequency 50HZ	
		Thermal magnetic trip unit	
		Flexible connection Collar terminals, front and rear connections, straight connections,	
		spreaders, plug in	
		Earth leakage protection	
		Rated insulation voltage 690V	
		Storage temperature -25°C to +70°C	
		Operating temperature -5°C to +60°C	
28	1	Insulating Stick for Medium Voltage Overhead Network (4- 36 KV) with a complete range of	
		accessories namely; operating hooks, voltage detector, trees trimmer.	
		Operation of disconnect switches	
		Use with voltage detectors	
		Application of LV/MV earthing devices	
		Maintenance work (Tree trimming, Conductor cleaning)	
		10.60m length when extended.	
		Complies with IEC 62193	
		Complies with IEC 60855-1	
		Complies with ASTM F 711	
		Complies with ASTM F 1826	
29	30	Waterproof Pole mounting enclosure	
20			
		300X200MM 5way enclosure	
00	45	0.5 - 440	
30	15	2.5m, 140mm power line wooden cross arm	
31	15	450mm threads rods	
32	15	1.5m copper earth spike rods	
33	200m	16 mm squared Insulated copper wire	
34	8	Galvanised pipe 20mm, 6m long	
35	1	Cordless Rotary Hammer Drill Kit	
		Rating: industrial	
		Batteries included 20V-7.5AH	
		Battery type: lithium ion  I ED better a power in disease.	
		LED battery power indicator	

Motor type: brushless     Impact energy: 2.6 Joules or above     No load energy: 1550 rpm or above
<ul> <li>No load speed: 1550 rpm or above</li> <li>Super-fast charger included</li> <li>Carry case included</li> </ul>

## NB: If the bidder does not quote for all the items, then they will be automatically disqualified.

#### Items must be SAB approved

- 1. Late, emailed, faxed, incomplete quotes will not be considered.
- 2. All quotes will be adjudicated and awarded in terms of the Dikgatlong Local Municipality Procurement and Supply Chain Management Policy, the Preferential Procurement Policy Framework Act, Act No. 5 of 2000 and the regulations promulgated under this Act. This bid is subject to the General Conditions of Contract and, if applicable, any other Special Condition of Contract.
- 3. Quotes must be valid for a period of 30 days
- 4. Suppliers must submit their quotes with the following documentation and or information:
- 4.1 A valid original Tax Clearance certificate or a valid tax pin.
- 4.2 A certificate certifying that the bidder has no undisputed commitments for Municipal services towards a municipality or service provider i.r.o. payments which are overdue more than 90 days; if the bidder is the lessee a valid lease agreement together with the municipal account of the landlord; or a letter from tribal authority if the service provider operates in rural area.
- 4.3 Certified evidence of B-B.B.E.E. contributor status by SANAS, IRBA or SANAS accredited agencies or valid affidavit order to claim HDI points.
- 4.4. MBD 4, 6.1, 8 and 9 must be fully completed and submitted together with a quotation.
- 4.5. Bidders must be registered on the Central Supplier Data Base.
- 4.6. The tender will be evaluated in terms of the 80/20 preference points system of which 80 points will be for price and 20 points for specific goals (HDI and Locality) as illustrated below.

SPECIFIC GOALS					
B-BBEE	(10)	Locality (10)			
B-BBEE Status Level of Contributor	Number of Points for HDI	Locality	Number of Points for Locality		
1 2	10 9	Within the boundaries of Dikgatlong Local Municipality	10		

SPECIFIC GOALS					
B-BBEE	(10)	Locality (10)			
B-BBEE Status Level of Contributor	Number of Points for HDI	Locality	Number of Points for Locality		
3	7	Within the boundaries of			
4	6	Frances Baard District	8		
5	4	Municipality			
6	3	Within the boundaries of	6		
7	2	Northern Cape			
8	1	Within the boundaries of South Africa	4		

- 5. The Municipality does not bind itself to accept the lowest or any bid and reserves the right to accept the whole or only part of a bid if (a) the bid amounts received are too high; (b) the bids do not comply with the specific bid goals; or (c) objective criteria exist which justify or necessitate the non-acceptance of any bids.
- 6. Address and the vat number (4450111283) of the municipality must appear on the quote.
- 7. Failure to meet the above requirements or submission of documents, except for submission of BBBEE certificate or Valid sworn affidavit will lead to disqualification of the quotation.

Enquiries must be directed to: SCM Office at Tel no: (053) 531 6520.

Ms B Tsinyane Acting Municipal Manager

Notice date: 07/02/2024